

LED TECHNOLOGY

3000 sqm
Area illuminated

Leader in sustainability 

BATTERY Line



X-BATTERY
4x100W LED - 7M
36H-72H

T-ZERO PRO




Operation: **100% BATTERY**
Power Battery Pack
24Vdc 400Ah (H36)
24Vdc 800Ah (H72)

X-BATTERY



4x100W LED - 7M
36H-72H

T-ZERO PRO



FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 5 sections manual vertical tower 7m, 340° rotatable
- Standard timer for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 22 units per truck**
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Certified wind stability up to 110 km/h
- 4 height adjustable stabilizers
- On board levels for guidance during stabilization
- **Running time 36h-72h**
- 24 volt DC Battery
- Floodlights 4x100W
- **Recharging in 12 hours**
- 230V 1PH built-in Battery charger



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)	
		1200x1200x2300 (LxWxH)		2500x2500x7000 (LxWxH)		750 (36H) - 998 (72H)
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)	
	Led	100W	4	65	3000	
Mast	Lifting method	Max Height	Max Wind Speed	Rotation	Safety break	
	Manual	7 m	110 km/h	340°	yes	
Battery	Type	Power Battery Pack	Model	Running time	Recharging time	Battery charger built-in
	AGM	24Vdc 400Ah (36H) 24Vdc 800Ah (72H)	Trime	36h - 72h	12 h	230V 1PH



TRIME® Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it
Lighting Towers