

TKS-60


water
nebulizer
50-60 m



30 kVA

Generator required

R.O.T. SYSTEM



Electric
Tilting System



Automatic
Oscillation 340°



Remote control
50m range

TKS-60

water
nebulizer
50-60 m



R.O.T. SYSTEM

- Electric Tilting System
- Automatic oscillation 0 - 340°
- Remote control, 50 mt range with all functions: switch on/off the fan, pump and electric rotation

FEATURE


- Integrated control panel
- SMART START SYSTEM
- Emergency stop button
- Phase inverter
- Water pump
- Water pressure Gauge
- Water Safety pressure switch
- Manual water drain system
- Central lifting eye
- Forklift pockets
- Stainless steel crown with 24 nozzles
- 3 height adjustable stabilizers
- Equipped with big size wheels for off-road site

SAFETY

- Reduce dust for healthy and safe environment
- Safety automatic clutch compliant with HSE norm
- Remote control with full operation
 - start/stop
 - tilt up/down
 - turn left/right/auto


OPTIONS

- 60 Hz
- External pump for chemicals additives
- Front jockey wheel



technical data		
Electric engine power	kW	22
Inlet plug	-	400V3P+N+T 50Hz 63A
Fan diameter	mm	900
Water consumption	l/m	37 - 43
Coverage (without wind)	m	50 - 60
Max. water throw height	m	20
Water connection	-	UNI 45 or STORZ or CAMLOCK
Min. inlet Water pressure	bar	1.0

technical data		
Generator required	kVA	30
Water inlet filter	Mesh	60
Y Filter	µm	500
Electric tilting system	-	0 - 35°
Automatic oscillation	-	0 - 340°
Dimensions min	mm	2077x1836x2230
Dimensions max	mm	2877x1836x2230
Weight	Kg	920



TRIME[®]
Dust Suppression

Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it